

- Industry 4.0
- Industry 5.0

MATRANDA

MTD_Slave Module

Article nr. : MTD_S04D04R00D04A02A



MTD Slave Module		MTD_S04D04R00D04A02A
Inputs digital galvanic isolated		4
Relay outputs		4
Digital outputs		X
Analogue inputs	4-20mA	4
Analogue outputs	4-20mA	2
PT100/ PT1000 inputs		X
Dimensions WxDxH		500x210x 500
Supply voltage		230Vac
P-Nom		15W
Ethernet ports		4
Ambient temperature		-10°C to 55°C
Protection class		IP66
Gland pass-through		Yes
Router		X

The MTD_Slave Module is equipped with galvanically isolated inputs and outputs.

As no heat is generated inside the MTD_Slave Module, the housing is splash-proof and equipped with cable glands.

Thus, the module fits into almost any manufacturing environment.

The MTD_Slave Module can also be converted to customer-specific requirements. However, different prices apply.

The MTD_Slave is usually used where no Logic Controller (PLC) is present.

The MTD_Slave Module features standard Matrand Software as well as control software. With this software, all inputs and outputs can be programmed according to the customer's specification.

The MTD_Slave has 2 Ethernet ports, one of which is connected to the MTD_Master Module or another MTD_Slave Module. The other Ethernet port is for connecting to another MTD_Slave Module.

The Ethernet connection for the MTD_Slave Modules has the same subnet address than the Ethernet connection for the other MTD_Slave Module and/or the MTD_Control Module.



MATRANDA, manufacturer and supplier of machine control and data collection with data transport.

Trade mark 'Matrand'. All our offers and contracts are subject to our General Terms & Conditions of Supply.

Contact : Newtonlaan 115 , 3584 BH Utrecht , +31 (0)84 – 872 89 38 , info@matrand.com , www.matrand.com